

SAFETY DATA SHEET (SDS)

Section 1. Identification

| | |
|--|---|
| Product identifier | TNI-88 |
| Other means of identification | 392 |
| Recommended use and restrictions on use | INJECTOR CLEANER |
| Initial supplier identifier | PROLAB TECHNOLUB INC. 4531 RUE INDUSTRIELLE, THETFORD MINES, (QUEBEC), G6H 2J1, CANADA TEL. (418) 423-2777 FAX : (418) 423-7619 |
| Emergency telephone number/restriction on use | Canada – CANUTEC 24 hour number 613-996-6666 |

Section 2. Hazard identification

Classification of hazardous product (name of the category or subcategory of the hazard class)

Flammable liquid (Category 3)
Aspiration hazard (Category 1)
Skin irritation (Category 2)
Eye irritation (Category 2A)
Specific target organ toxicity – single exposure (Category 3), Central nervous system

Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)



Danger

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands/nails/face thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear gloves/protective clothing/eye protection/face protection. P301 + P310 IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P302 + P352 IF ON SKIN: Wash with plenty of water. P332 + P313 IF SKIN irritation occurs: Get medical attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P305+P351+P338 IF IN EYES, Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical attention. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a doctor if you feel unwell. P370 + P378 In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish. P403 + P233 + P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other hazards known | None

Section 3. Composition/information on ingredients

| Chemical name (common name/synonyms) | CAS number or other | Concentration (%) |
|---|----------------------------|--------------------------|
| Aliphatic naphtha | 64741-65-7 | 60-100 |
| Aromatic naphtha | 64742-94-5 | 5 |
| Kerosene | 64742-47-8 | 5 |

Section 4. First-aid measures

| | |
|---------------------|---|
| Inhalation | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell. |
| Ingestion | IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. |
| Skin contact | IF ON SKIN, Wash with plenty of water for several minutes (15-20). If skin irritation occurs: Get medical attention. |
| Eye contact | IF IN EYES, Rinse cautiously with water for several minutes (15-20). Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. |

Most important symptoms and effects (acute or delayed) | May be harmful if swallowed and enters airways.

Indication of immediate medical attention/special treatment | In all cases, call a doctor. Do not forget this document.

Section 5. Fire-fighting measures

Specific hazards of the hazardous product (hazardous combustion products)

Carbon oxides and other irritant/toxic gases and fumes.

Suitable and unsuitable extinguishing media

In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish.

Special protective equipment and precautions for fire-fighters

During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

| Section 6. Accidental release measures | | | |
|---|-----------------|--|------------------|
| Personal precautions, protective equipment and emergency procedures | | | |
| Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8). | | | |
| Methods and materials for containment and cleaning up | | | |
| Avoid release to the environment. Collect spillage. Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required. | | | |
| Section 7. Handling and storage | | | |
| Precautions for safe handling | | | |
| Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wash hands/nails/face thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8. | | | |
| Conditions for safe storage, including any incompatibilities | | | |
| Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks. | | | |
| Section 8. Exposure controls/Personal protection | | | |
| Control parameters (biological limit values or exposure limit values and source of those values) | | | |
| Exposure limits: None | | | |
| Appropriate engineering controls | | | |
| Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. | | | |
| Individual protection measures/personal protective equipment | | | |
| Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use. | | | |
| Section 9. Physical and chemical properties | | | |
| Appearance, physical state/colour | Yellow liquid | Vapour pressure | Not available |
| Odour | Characteristic | Vapour density | Heavier than air |
| Odour threshold | Not available | Relative density | 0.7657 |
| pH | Not available | Solubility | Not available |
| Melting/freezing point | -53°C | Partition coefficient - n-octanol/water | Not available |
| Initial boiling point/range | Not available | Auto-ignition temperature | Not available |
| Flash point | 52°C Closed cup | Decomposition temperature | Not available |
| Evaporation rate | Not available | Viscosity | 1.75 cSt @ 40°C |
| Flammability (solids and gases) | Not available | VOC | Not available |
| Upper and lower flammability/explosive limits | Not available | Other | None known |
| Section 10. Stability and reactivity | | | |
| Reactivity | | | |
| Does not react under the recommended storage and handling conditions prescribed. | | | |
| Chemical stability | | | |
| Stable under the recommended storage and handling conditions prescribed. | | | |
| Possibility of hazardous reactions | | | |
| Accumulation of flammable if product is heated. | | | |
| Conditions to avoid (static discharge, shock or vibration) | | | |
| Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. | | | |
| Incompatible materials | | | |
| Oxidizing materials; etc. | | | |
| Hazardous decomposition products | | | |
| None known | | | |

| Section 11. Toxicological information | |
|--|---|
| Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact) | |
| May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. | |
| Symptoms related to the physical, chemical and toxicological characteristics | |
| Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing; Respiratory tract irritation, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches. | |
| Delayed and immediate effects (chronic effects from short-term and long-term exposure) | |
| Skin Sensitization – No data available; Respiratory Sensitization – No data available; Germ Cell Mutagenicity – No data available; Carcinogenicity – No ingredient listed by IARC, ACGIH, NTP or OSHA; Reproductive Toxicity – No data available; Specific Target Organ Toxicity — Single Exposure – Central nervous system; Specific Target Organ Toxicity — Repeated Exposure – No data available; Aspiration Hazard – Possible; Health Hazards Not Otherwise Classified – No data available. | |
| Numerical measures of toxicity (ATE; LD₅₀ & LC₅₀) | |
| None ATE not available in this document. | |
| Section 12. Ecological information | |
| Ecotoxicity (aquatic and terrestrial information) | No data available for this product. |
| Persistence and degradability | No data available for this product. |
| Bioaccumulative potential | No data available for this product. |
| Mobility in soil | No data available for this product. |
| Other adverse effects | No data available |
| Section 13. Disposal considerations | |
| Information on safe handling for disposal/methods of disposal/contaminated packaging | |
| Dispose of contents/container into safe container in accordance with local, regional or national regulations. | |
| Section 14. Transport information | |
| UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations | |
| UN1268; PETROLEUM DISTILLATES, N.O.S.; CLASS 3; PG III | |
| UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime) | |
| UN1268; PETROLEUM DISTILLATES, N.O.S.; CLASS 3; PG III | |
| UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air) | |
| UN1268; PETROLEUM DISTILLATES, N.O.S.; CLASS 3; PG III | |
| Special precautions (transport/conveyance) | May also be shipped as NOT REGULATED by ground in accordance with TDG. |
| Environmental hazards (IMDG or other) | None |
| Bulk transport (usually more than 450 L in capacity) | Possible |
| Section 15. Regulatory information | |
| Safety/health Canadian regulations specifics | Refer to Section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR). |
| Environmental Canadian regulations specifics | Refer to Section 3 for ingredient(s) of the DSL |
| Safety/health/environmental outside regulations specifics | |
| United States OSHA information: This product is regulated according to OSHA (29 CFR). United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14. United States TCSA information: Refer to the ingredients listed in Section 3. National Fire Protection Association (NFPA): HEALTH: 1 FLAMMABILITY: 2 INSTABILITY: 0 SPECIAL HAZARDS: Refer to Section 2 & 3. HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe California Proposition 65: This product contains a material known to the State of California to cause cancer or other reproductive harm. | |

Section 16. Other information

Date of the latest revision of the safety data sheet | January 05, 2021.

References | Safety Data Sheets from manufacturer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.

Abbreviations

| | |
|-------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists |
| ATE | Acute toxicity estimate |
| CAS | Chemical Abstract Service |
| DSL | Domestic Substance List |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods Code |
| LC | Lethal concentration |
| LD | Lethal Dosage |
| NIOSH | National Institute for Occupational Safety and Health |
| NTP | National Toxicology Program (U.S.A.) |
| OSHA | Occupational Safety and Health Administration (U.S.A.) |
| PEL | Permissible Exposure Limit |
| STEL | Short-term Exposure Limit |
| TDG | Transport of dangerous goods in Canada |
| TLV | Threshold Limit Value |
| TSCA | Toxic Substances Control Act |
| TWA | Time Weighted Average |
| WHMIS | Workplace Hazardous Materials Information System |

The information presented herein has been compiled from sources considered dependable and is accurate to the best of **PROLAB TECHNOLOG INC.**'s knowledge. **PROLAB TECHNOLOG INC.** Makes no warranty whatever expresses or implied of merchantability or fitness for the particular purpose. The information relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Customers are encouraged to conduct their own tests. Before using the product, read its label. **PROLAB TECHNOLOG INC.** Assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.